

DATABLAD



MC200209 - Kabel 7,5m til KDM20 Eurofast

Data

Gobale egenskaper

Standard	EN IEC 61076-2-101
Versjon	rett
Bruttovekt	240 g

Gobale egenskaper - Karakteristikker

Halogen free	Ja
Cable drag chain suitable	Ja
Antall ledere	8

Mekaniske data

Tiltrekkingsmoment, maksimum	1 Nm
------------------------------	------

Mechanical data - Connection technique

Lengde for kabel	7,5 m
Ledertverrsnitt	0,25 mm ²
Cable diameter	5,9 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Colour of the Cable mantle	Black
Materiale for kabelmantel	PUR

Mekaniske data - Stikkontakt side A

Connector typ	Female connector, M12
Design	straight
Connector coding	A
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black

Mekaniske data - Stikkontakt side B

Connector typ	Male connector, M12
Design	straight
Connector coding	A
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black

Omgivelsesbetingelser

Tetthetsgrad	IP65 IP67 IP69
Ambient temperature (Connector)	-30 ... +90 °C
Ambient temperature (fixed)	-50 ... +90 °C
Ambient temperature (moved)	-30 ... +90 °C
Ambient temperature (drag chain)	-25 ... +60 °C

Elektriske data

Termisk teststrøm	2 A
Rated operating voltage	30 VAC
Rated operating voltage	30 VDC
driftsstrøm	2 000 mA

Pin-tildeling

PIN 1	Hvit
PIN 2	Brun
PIN 3	grønn
PIN 4	gul
PIN 5	Grå
PIN 6	Rosa
PIN 7	Blå
PIN 8	rød

Bilder

Produktbilde (enkelt katalogbilde)

